

N. 1101-CPR-15-10

1. Unique identification code of the product-type: **FASSACOUCHÉ**
2. Intended use: **One coat rendering mortar (OC)**
3. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY – www.fassabortolo.com**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **4**
6. Harmonised standard: **EN 998-1: 2010**

Notified bodies: NA

7. Declared performances:

Reaction to fire	A1	Adhesion after weathering cycles	≥ 0,3 N/mm²
Water absorption	W2	Thermal conductivity λ	0,43 W/mK (tabulated value)
Water permeability after weathering cycles	≤ 1 ml/cm² after 48 h	Durability	NPD
Water vapor permeability	35	Dangerous substances	See MSDS
Adhesion	≥ 0,3 N/mm² - FP:B		

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Francesco Basile

Research & Development and Quality System Director

Spresiano (TV), 01/10/2015

FASSA S.r.l.
Via Lazzaris n° 3
31027 SPRESIANO (TV)
Partita IVA 02015890268



FASSA S.r.l.